

Related Products and Services

- ▶ **Omni-ID IQ 600** - Ultrathin label providing on metal tag functionality, low cost and hassle free deployment.
- ▶ **Omni-ID Flex 600** - Low profile, cost effective tag, ideal for office equipment and portal setups.
- ▶ **Omni-ID Flex 1200** - Low cost alternative to hard tags for applications requiring read ranges of up to 12 meters.
- ▶ **Service Bureau** - Omni-ID offers a full service bureau for printing and pre-encoding Omni-ID tags at point of manufacture.



Environmental Specifications

Storage Temperature -40 ° to +85 °C

Operation Temperature¹ -40 ° to +85 °C




Survivability -40 ° to +85 °C

IP Rating IP68

Shock and Vibration MIL STD 810-G

Attachment Film adhesive (std)

Certifications




 RoHS approved
 CE approved
 ATEX/IECEX certified (option)
 US&Canada (C1D1/D2) certified (option)

Warranty 1 year

¹ Excludes adhesive options, consult adhesive data sheets for recommended temperature ratings.

Ordering Information

Order code 151 - US, EU

Order options

- :303 (Customization)
- :304 (ATEX/IECEX certified)
- :307 (US&Canada (C1D1/D2) certified)
- :536 (Textured surface adhesive)

Supplied in rolls of 900 tags. Minimum order quantity is 1 roll.

Omni-ID office locations: **US | UK | China | India | Germany**
 For product or technology inquiries email: sales@omni-id.com